



RS-100 STRIPPING HEAD

RS-100 STRIPPING HEAD - NO CORE CHARGE REQUIRED

Mitey Titan RS Stripping Heads are wellbore pressure energized stripping heads that do not require any hydraulics to contain up to 1,200 PSI Dynamic Pressure and up to 3,000 PSI Static Pressure.

HIGHLIGHTED FEATURES

- Rubber Stripper / Pack-off Head is Wellbore Energize Seal
- Most cost-effective, safe & reliable means of Sealing pipe for tripping in / out under pressure with the conjunction of Annular BOP
- RS-100 Sealing capacity: 1,200 psi Dynamic & 3,00 psi Static with single RS-100 system
- Primary seal contact wider than 1 inch and secondary seals activated at low pressure to create a positive seal in all applications
- RS Element Bolt Pattern matches all exiting RS Stripping head design
- There is No Core charge
- Custom design as per client requirements

RS-STRIPPING HEAD



APPLICATIONS

- Drilling Rigs
- Hydraulic Workover Units
- Sand Clean Outs
- Service Rigs
- Snubbing Units
- Under-Balance Applications

RS-100 - STRIPPING HEADS

RS SIZE	PART NUMBER
4.06-5K"	RS - 2509
7.06-3K"	RS01 - 1112A
7.06-5K"	RS01 - 1113A
11-5K"	RS - 2123
13-5K"	RS01 - 1115A

WHY PURCHASE MTI RS-STRIPPING HEADS?

Advancements in technology due to their constant evolution, contributing to rigorous building standards and high quality. Key features are easy replacement of Rubber Elements, Labyrinth Sealing, and standard 1" and 2" ports which allow any client to install side outlets without any modifications to the Stripping Heads.

RS-BAG



RS-100 - MEASUREMENTS

PIPE SIZE	PART NUMBER
1.66"	RS - 1106P
1.90"	RS - 1107P
2.375"	RS - 1108P
2.875"	RS - 1109P
3.500"	RS - 1110P
4.500"	RS - 1111P